



an EnerSys® company

Cordex® HP 1.2kW

1RU Integrated Shelf System with GMT Distribution



- Single shelf modular rectifier solution provides up to 75A capacity @ -48VDC for various small power applications
- High efficiency design for reduced operating expenses
- High temperature rated, fan-cooled design for harsh outdoor installations
- Wide range AC input and IEC line cords for multiple AC services
- Front accessible fuse distribution for space restricted enclosures

Cordex® High-Performance (HP) rectifiers make a proven, reliable platform even better, with significant advancements in efficiency and performance.

Featuring a compact, fan-cooled design, HP rectifiers open the possibility to wider ranges of applications and immediate OPEX/CAPEX savings, reducing total cost of ownership and impact on the environment.

Designed specifically for restricted space installations, this 48VDC power and distribution system incorporates the reliable 48V, 1.2kW Cordex® rectifier modules and front accessible fuse distribution connections. The system is a perfect solution for small 48VDC power applications such as customer premise, xDSL, FTTx, distributed node B and microwave. High efficiency, high temperature operation, and a small 1RU footprint make the system ideal for harsh outside plant installations.

The 19/23" universal rack mount power system accommodates up to three Cordex® HP 48V-1.2kW rectifiers and a modular Cordex® CXCM1 HP controller, with GMT Fuse distribution, in a compact 1RU package.

Cordex® HP 1.2kW 1RU Integrated Shelf System with GMT Distribution

P/N: 030-851-20-XXX

| Electrical | |
|--|--|
| Input Voltage | Operating: 90 to 300VAC [See output power for power derating] |
| Input Current (per module): | 7.5A Maximum (176 to 300VAC) 6.0A Maximum (90 to 176VAC) |
| Efficiency: | >93% at 240VAC Input and 40-100% load |
| Power Output (per module): | 1200W (176 to 300VAC input) 600W (110 to 130VAC Input) |
| *Power de-rated linearly from 1200-600W (176 to 130VAC input) *Power de-rated linearly from 600-500W (110 to 90VAC input) | |
| Current Output (per module): | 25A @ 48VDC (176 to 300VAC input) 12.5A @ 48VDC (110 to 130VAC Input) |
| Mechanical | |
| Dimensions: | mm: 44H x 439.5W x 335D inches: 1.75H x 17.3W x 13.2D |
| *Note: Excludes Rectifier Front Handle and Optional Kydex Cover | |
| Mounting: | 19" or 23" rack, 6" offset (center), EIA rack spacing |
| Weight: | Shelf: 3kg (6.6lbs) Rectifier: 1.23kg (2.72lbs) |
| Connections | |
| GMT Fuse (Load): | (7) Positions (8A): Terminal block (#16 to #30 AWG) (1) Position (10A): Terminal block (#14 to #26 AWG) |
| Battery: | ¼" on ¾" center 2-hole lugs |
| AC Input: | Dual IEC-60320-C20 |
| Alarms: | Terminal block (#16 to #26 AWG) |
| *Note: Shelf P/Ns do not include rectifier module, GMT Fuses, or AC Line Cords | |

| Environmental | |
|--------------------------|--|
| Temperature: | Standard: -40 to 65°C (-40 to 149°F) Extended: -40 to 80°C (-40 to 176°F) (de-rated output power) |
| Storage: | -40 to 80°C (-40 to 176°F) |
| Humidity: | 0 to 95% RH non-condensing |
| Elevation: | -500 to 2800m (-1640 to 9186ft) |
| Cooling: | Fan cooled (front to rear) |
| Heat Dissipation: | 886.2 BTU hour/system max. |
| Related Components | |
| 010-619-20-041: | Cordex® HP 1.2kW 48VDC rectifier |
| 0180054-001: | CXCM1 HP Cordex® Controller |
| 877-690-19: | 5-15P (120V) line cord, 2.5m |
| 877-790-19: | Universal line cord, flying leads, 3.5m |
| 747-622-20-000: | Blank plate |
| 5610638-001: | Kydex rear cover |
| 036-201-20-000: | CXCM1 I/O terminal block kit |
| Agency Compliance | |
| Safety: | <ul style="list-style-type: none"> • CSA C22.2 No 60950-1-03 • CE marked |
| NEBS: | <ul style="list-style-type: none"> • GR-1089-CORE • GR-63-CORE |



Rear view: Cordex® HP 48V Integrated 75A System



an EnerSys® company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

07/2020
#0480007-00 REV E